



### AMS-250

Design	2-driver, die-cast chassis / mounting bracket, 2-way in-ceiling / in-wall
Crossover	2nd-order electro-acoustic at 1.7 kHz
High-Frequency Driver	25-mm (1 in) PTD™ dome with die-cast heatsink faceplate
Bass/Midrange Driver(s)	die-cast chassis, 165-mm (6-1/2 in) mineral-filled polypropylene cone
Finishes	White, paintable
Low Frequency Extension	50 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 65 Hz - 20 kHz
Frequency Rresponse 30 off axis	±2 dB from 65 Hz - 18 kHz
Sensitivity-Room/Anechoic	90 dB / 86 dB
Suitable Amplifier Power Range	120 - 15 watts
Maximum Input Power	90 watts
Impedance	Compatible with 8 ohms
Minimum Internal Volume Required	12 L / 0.4 cu ft
Cutout Dimensions Diameter or Height x Width	26 cm x 17.2 cm (Height x Width) 10-1/4 in x 6-3/4 in (Height x Width)
Pre-Installation Brackets	-
Height,Width or Diameter	28.6 cm x19.8 cm (Height x Width) 11-1/4 in x7-13/16 in (Height x Width)
Minimum Mounting Depth	6.7 cm /2-5/8 in
Weight	13lb / 5.90kg