



gTP7 is international voltage compatible

Welcome to Convenience.

Simple, fun, efficient. Three words that perfectly describe the ELAN gTP7 7" touch panel for the ELAN! integration system. Designed to reverse the trend towards using wall mounted iPads by providing an attractive, dedicated user interface the gTP7 is attractive and flexible enough to use in any project.

Using a function specific interface like the gTP7 provides the end-user with a much richer experience. The gTP7 wakes as the hand approaches and offers a seven button fly-out keypad that may operate media favorites, trigger lighting scenes, installer programmed Event Maps or control virtually anything connected to the system. The fly-out keypad gives way to the award winning g! user interface where they may operate all of the systems in their home.

The gTP7 is designer friendly as well. By taking advantage of the unique g! compatibility with both portrait and landscape user interfaces, the gTP7 is the first wall mounted touch panel to be equally at home in both a horizontal and a vertical arrangement. This provides installation flexibility that allows a 7" touch panel to be located in most areas that would accommodate a 2 gang wall plate.

As with all the ELAN "g" series products, the gTP7 was designed to be easy and flexible. It starts with mounting, using a standard 2 gang (US) box, which means no custom bracket to order or stock. The back box centers with the touch panel making it much easier to place during pre-wire. An included mounting ring provides support for the gTP7 over smooth and

uneven wall surfaces. The gTP7 simply snaps into the bracket - no special tools needed. The TP7 may be powered locally using a 12VDC power supply (not included) and connected to the g! controller over Wi-Fi, or you may power over Ethernet and utilize a single wire hookup.

gTP7's are available with black or white trim and are compatible with all gSC series controllers and includes special capabilities like an IP camera, a speaker, and echo cancelling microphones for use with upcoming g! features. Try one, or better yet, let your customer try one, and we are sure that they will find the gTP7 to be a superior experience.

gTP7 Wall Mounted Touch Panel



ORDER NO. gTP7

FEATURES

- 7" diagonal viewable area LCD touchscreen interface
- Contemporary, sleek industrial design
- Edge to edge glass
- Capacitive sense touchscreen
- Proximity sensor to wake from sleep without touching as hand approaches
- 7 button flyout provides instant access to lighting scenes, favorites or Event Maps
- Mounts into drywall, brick, stone, plaster, and wood, using a standard 2g U.S. junction box
- Portrait or landscape mounting
- Supports TCP/IP communication
- Wi-Fi support
- Plug and play operation with ELAN g! Software
- Locally powered (optional)
- Displays MJPEG and H.264 video codec's from IP CCTV cameras
- Near field focus wide angle color camera with MJPEG IP-CCTV output
- Available in white and black bezel

SPECIFICATIONS	
Dimensions	Overall 8" wide x 5" height, mounting depth 1.75"
Screen size	7-inch diagonal, 16:9 widescreen
Resolution	800W x 480H
Microphone	Dual Digital Beam Forming for Field Pickup
Speaker	2W integrated
Camera	640X x 480H
Network	10/100 Ethernet / 802.11 B/G/N WiFi

SPECIFICATIONS	
Type	LAN/PoE: RJ-45
Power Requirements	PoE (Power over Ethernet) IEEE 802.3at, 13w maximum draw (@48V === 270mA max)
USB	USB Type A
Audio Out	1/8" stereo mini (Future Use)

POWER REQUIREMENTS	
Direct	12V ===, 1 A. Phoenix 2 pin screw terminal connector
PoE	IEEE802.3at, (power over Ethernet) 13w maximum draw (@48V === 270 mA max)
Included in box	(1) gTP7 touchpanel (1) Mounting bracket (4) Mounting screws

