



AMS-150R-SM

Design	Single speaker system with stereo L/R inputs, 3-driver, 2 x 2-way in-ceiling / in-wall, GRIP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
Frequency Response On-Axis	±2 dB from 60 Hz - 22 kHz
Frequency Response 30° Off-Axis	±2 dB from 60 Hz - 16 kHz
High Frequency Driver	Two 25-mm (1 in) S-PAL™ domes, die-cast heatsink
Mid/Bass Frequency Driver	Dual voice-coil, 210-mm (8 in) mineral-filled polypropylene cone
Low Frequency Extension	45 Hz (DIN)
Sensitivity Room / Anechoic	91 dB / 87 dB
Impedance	Compatible with 4 ohms Mono; 8 ohms / channel Stereo Input
Suitable Amplifier Power Range	15 - 110 watts Mono; 15 - 55 watts / channel Stereo Input
Maximum Input Power	80 watts Mono; 40 watts / channel Stereo Input
Finishes	White, paintable
Weight	4.6 lbs. (2.1 kg)
Overall Dimensions	8.9375" (22.6cm) Diameter
Cut-Out Dimensions	7.875" (20.0cm) Diameter
Minimum Mounting Depth	3.25" (8.3cm)
Depth required is the distance between 1/2" drywall, or similar material	
Minimum Internal Volume Required	0.70 cu ft (20 L)

Specifications are subject to change without notice.

