



AMS-150RX

Design	2-driver, 2-way in-ceiling / in-wall, stainless steel grilles, Xtreme Moisture Application™ version, GRIP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
Frequency Response On-Axis	±2 dB from 60 Hz - 22 kHz
Frequency Response 30° Off-Axis	±2 dB from 60 Hz - 20 kHz
High Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast heatsink
Mid/Bass Frequency Driver	210-mm (8 in) mineral-filled polypropylene cone
Low Frequency Extension	45 Hz (DIN)
Sensitivity Room / Anechoic	91 dB / 87 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15 - 110 watts
Maximum Input Power	80 watts
Finishes	White, paintable
Weight	3.9 lbs. (1.8 kg)
Overall Dimensions	8.9375" (22.6cm) Diameter
Cut-Out Dimensions	7.875" (20.0cm) Diameter
Minimum Mounting Depth	3.25" (8.3cm)
Depth required is the distance between 1/2" drywall, or similar material.	
Minimum Internal Volume Required	0.70 cu ft (20 L)

Specifications are subject to change without notice.

