



AMS-350

| | |
|--|---|
| Design | 3-driver, 2-way in-wall / in-ceiling, die-cast chassis / mounting bracket |
| Crossover | 2nd-order electro-acoustic at 2.0 kHz |
| Frequency Response On-Axis | ±2 dB from 55 Hz - 22 kHz |
| Frequency Response 30° Off-Axis | ±2 dB from 55 Hz - 20 kHz |
| High Frequency Driver | 25-mm (1 in) S-PAL™ dome, die-cast heatsink |
| Mid/Bass Frequency Driver | Two 210-mm (8 in) mineral-filled polypropylene cones |
| Low Frequency Extension | 35 Hz (DIN) |
| Sensitivity Room / Anechoic | 94 dB / 90 dB |
| Impedance | Compatible with 8 ohms |
| Suitable Amplifier Power Range | 15 - 200 watts |
| Maximum Input Power | 150 watts |
| Finishes | White, paintable |
| Weight | 12.8 lbs. (5.8 kg) |
| Overall Dimensions | 20.125" (51.0cm) Height 9.125" (23.0cm) Width |
| Cut-Out Dimensions | 19.125 " (48.6cm) Height, 8.0625 " (20.5cm) Width |
| Minimum Mounting Depth | 3" (7.6cm) |
| Depth required is the distance between 1/2" drywall, or similar material | |
| Minimum Internal Volume Required | 1.4 cu ft (40 L) |

Specifications are subject to change without notice.

