



## MINI MONITOR

Design	2-driver, 2-way bass reflex, quasi-3rd-order resistive port, bookshelf / stand-mounted
Crossover	2nd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) S-PAL™, satin-anodized pure-aluminum dome tweeter, ferro-fluid cooled and damped
Midrange Driver	N/A
Bass / Midrange Driver	165-mm (6-1/2 in) S-PAL™ satin-anodized pure-aluminum cone, 25-mm (1 in) high-temperature voice-coil, oversize ceramic / ferrite magnets, GRIP™ glass-reinforced injection-molded polymer chassis
Bass Driver	N/A
Low-Frequency Extension	42 Hz
Frequency Response On-Axis	±2 dB from 75 Hz – 22 kHz
Frequency Response 30° Off-Axis	±2 dB from 75 Hz – 18 kHz
Sensitivity – Room / Anechoic	90 dB / 87 dB
Suitable Amplifier Power	15 – 100 watts
Maximum Input Power	80 watts
Impedance	Compatible with 8 ohms
Dimensions (h x w x d)	34.3 cm x 19.4 cm x 26.5 cm, 13-1/2 in x 7-5/8 in x 10-1/2 in
Weight (unpacked)	7.7 kg / 17 lb per speaker
Finishes	Black Ash, Heritage Cherry

Specifications are subject to change without notice.

