



## MONITOR 9

Design	4-driver, 2-1/2-way bass reflex, quasi-3rd-order resistive port, floorstanding model
Crossover	3rd-order electro-acoustic at 2.0 kHz; 2nd-order electro-acoustic at 700 Hz (lower bass drivers)
High-Frequency Driver	25-mm (1 in) S-PAL™ satin-anodized pure-aluminum dome tweeter, ferro-fluid cooled and damped
Midrange Driver	N/A
Bass / Midrange Driver	140-mm (5-1/2 in) S-PAL™ satin-anodized pure-aluminum cone, 25-mm (1 in) high-temperature voice-coil, oversize ceramic / ferrite magnets, GRIP™ glass-reinforced injection-molded polymer chassis
Bass Driver(s)	Two 140-mm (5-1/2 in) carbon-infused polypropylene cones, 25-mm (1 in) high-temperature voice-coils, oversize ceramic / ferrite magnets, GRIP™ glass-reinforced injection-molded polymer chassis
Low-Frequency Extension	31 Hz
Frequency Response On-Axis	±2 dB from 46 Hz – 22 kHz
Frequency Response 30 Off-Axis	±2 dB from 46 Hz – 18 kHz
Sensitivity – Room / Anechoic	91 dB / 88 dB
Suitable Amplifier Power	15 – 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Dimensions (h x w x d)	101.6 cm x 17.5 cm x 26.5 cm, 40 in x 6-7/8 in x 10-1/2 in
Weight (unpacked)	19.1 kg / 42 lb per speaker
Finishes	Black Ash, Heritage Cherry

Specifications are subject to change without notice.

