



SA-10R V3

Design	2-driver, 2-way in-ceiling / in-wall, GRIP™ chassis / mounting bracket
Crossover	3rd-order electro-acoustic at 2.5 kHz
Frequency Response On-Axis	±2 dB from 60 Hz - 22 kHz
Frequency Response 30° Off-Axis	±2 dB from 60 Hz - 20 kHz
High Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink faceplate
Mid/Bass Frequency Driver	165-mm (6-1/2 in) S-PAL™ cone, 38-mm (1-1/2 in) voice-coil, GRIP™ chassis
Low Frequency Extension	40 Hz (DIN)
Sensitivity Room / Anechoic	91 dB / 87 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15 - 150 watts
Maximum Input Power	90 watts
Finishes	White, paintable
Weight	4.3 lbs. (2.0 kg)
Overall Dimensions	17.6875" (19.5cm) Diameter
Cut-Out Dimensions	6.75" (17.25cm) Diameter
Minimum Mounting Depth	3.4375" (8.7cm)
Depth required is the distance between 1/2" drywall, or similar material.	
Minimum Internal Volume Required	0.42 cu ft (12 L)

Specifications are subject to change without notice.

