



## SA-15R-30 V3

Design	Guided Soundfield™ system, 2-driver, 2-way in-ceiling, drivers mounted at 30° relative to mounting surface, GRIP™ chassis / mounting bracket
Crossover	3rd-order electro-acoustic at 2.5 kHz
Frequency Response On-Axis	±2 dB from 58 Hz - 22 kHz
Frequency Response 30° Off-Axis	±2 dB from 58 Hz - 17 kHz
High Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink faceplate
Mid/Bass Frequency Driver	210-mm (8 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, GRIP™ chassis
Low Frequency Extension	37 Hz (DIN)
Sensitivity Room / Anechoic	92 dB / 88 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15 - 160 watts
Maximum Input Power	100 watts
Finishes	White, paintable
Weight	6.4 lbs. (2.9 kg)
Overall Dimensions	11.625" (29.6cm) Diameter
Cut-Out Dimensions	10.625" (14.3cm) Diameter
Minimum Mounting Depth	5.625" (27.0cm)
Depth required is the distance between 1/2" drywall, or similar material.	
Minimum Internal Volume Required	0.70 cu ft (20 L)

Specifications are subject to change without notice.

