



PRESTIGE 75F

Design	4-driver, 2-1/2 way floorstanding
Crossover	2nd order electro-acoustic at 2.0kHz (tweeter/mid); 2nd order @500Hz (mid/bass)
Frequency Response On-Axis	±2dB from 40 Hz - 20 kHz
Frequency Response 30° Off-Axis	±2dB from 40 Hz - 17 kHz
High Frequency Driver	1" (25mm) X-PAL dome, ferro-fluid damped / cooled, Perforated Phase-Aligning (PPA) Tweeter Lens, Finite Element Analysis (FEA) optimized pole piece assembly
Mid/Bass Frequency Driver	6.5" (165mm) X-PAL driver, overmolded Active Ridge Technology (ART) surround, SHOCK-MOUNT Isolation Mounting System, 1.5" high-temp voice coil
Low Frequency Driver	Two 6.5" (165mm) X-PAL driver, overmolded Active Ridge Technology (ART) surround, SHOCK-MOUNT Isolation Mounting System, 1.5" high-temp voice coil
Low Frequency Extension	29 Hz (DIN)
Sensitivity Room / Anechoic	93 dB / 90 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15 - 350 watts
Maximum Input Power	200 watts
Finishes	Gloss: Piano Black & Midnight Cherry. Satin: Walnut & Black Walnut
Weight	57 lbs. (26 kg)
Dimensions H x W x D	40" × 8.125" × 12.5", (101.6cm × 20.6cm × 31.8cm)

Specifications are subject to change without notice.

