



CI Elite E80-IW

Design	2-driver, 2-way in-wall, SHOCK-MOUNT™ Isolation Mounting System, die-cast aluminum baffle
Crossover	3rd-order electro-acoustic at 2.0 kHz
Frequency Response On-Axis	±3 dB from 57 Hz - 22 kHz
Frequency Response 30° Off-Axis	±3 dB from 57 Hz - 18 kHz
High Frequency Driver	1" (2.5cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, Perforated Phase-Aligning (PPA™) Tweeter Lens
Mid/Bass Frequency Driver	8" (20.3cm) X-PAL™ driver, overmolded Active Ridge Technology (ART™) surround, 1.5" high-temp voice coil, die-cast aluminum chassis
Low Frequency Extension	33 Hz
Sensitivity Room / Anechoic	92 dB / 88 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15-180 W
Maximum Input Power	120 W
Finishes	White, paintable grille, black speaker
Weight	8.6 lbs. (3.9 kg)
Overall Dimensions	12.625" (32.1cm) Height, 9.25" (23.4cm) Width
Cut-Out Dimensions	11.56" (29.3cm) Height, 8.06" (20.5cm) Width
Minimum Mounting Depth	3.375" (8.6cm)
Depth required is the distance between 1/2" drywall, or similar material	

Specifications are subject to change without notice.

