



CI Pro P65-R

Design	2-driver, 2-way in-ceiling, SHOCK-MOUNT™ Isolation Mounting System, nylon-blended rigid baffle
Crossover	2nd-order electro-acoustic at 2.5 kHz
Frequency Response On-Axis	±3 dB from 75 Hz - 22 kHz
Frequency Response 30° Off-Axis	±3 dB from 75 Hz - 18 kHz
High Frequency Driver	1" (2.5cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, Perforated Phase-Aligning (PPA™) Tweeter Lens
Mid/Bass Frequency Driver	6.5" (16.5cm) mineral-filled polypropylene cone, overmolded Active Ridge Technology (ART™) surround, die-cast aluminum chassis
Low Frequency Extension	41 Hz
Sensitivity Room / Anechoic	91.5 dB / 87.5 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15-100 W
Maximum Input Power	80 W
Finishes	White, paintable grille, black/grey speaker
Weight	5.7 lbs. (2.6 kg)
Overall Dimensions	8.875" (22.6cm) Diameter
Cut-Out Dimensions	7.75" (19.7cm) Diameter
Minimum Mounting Depth	3.625" (9.2cm)
Depth required is the distance between 1/2" drywall, or similar material	

Specifications are subject to change without notice.

