



CI Pro P80-A

Design	2-driver, 2-way in-ceiling, 30°-Angled Guided Soundfield™ System, SHOCK-MOUNT™ Isolation Mounting System, nylon-blended rigid baffle
Crossover	2nd-order electro-acoustic at 2.0 kHz
Frequency Response On-Axis	±3 dB from 58 Hz - 22 kHz
Frequency Response 30° Off-Axis	±3 dB from 58 Hz - 18 kHz
High Frequency Driver	1" (2.5cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, Perforated Phase-Aligning (PPA™) Tweeter Lens
Mid/Bass Frequency Driver	8" (20.3cm) mineral-filled polypropylene cone, overmolded Active Ridge Technology (ART™) surround, die-cast aluminum chassis
Low Frequency Extension	39 Hz
Sensitivity Room / Anechoic	93 dB / 89 dB
Impedance	Compatible with 8 ohms
Suitable Amplifier Power Range	15-110 W
Maximum Input Power	80 W
Finishes	White, paintable grille, black/grey speaker
Weight	6.6 lbs. (4.1 kg)
Overall Dimensions	12.625" (32.0cm) Diameter
Cut-Out Dimensions	11.4375" (29.1cm) Diameter
Minimum Mounting Depth	5.625" (14.3cm)
Depth required is the distance between 1/2" drywall, or similar material	

Specifications are subject to change without notice.

