



SA-25

| | |
|----------------------------------|--|
| Design | 2-driver, 2-way in-wall / in-ceiling, die-cast chassis / mounting bracket |
| Crossover | 3rd-order electro-acoustic at 2.0 kHz |
| High-Frequency Driver | 25-mm (1 in) G-PAL™ dome, die-cast heatsink, ferro-fluid cooled |
| Bass/Midrange Driver(s) | 165-mm (6-1/2 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, die-cast chassis |
| Low Frequency Extension | 39 Hz (DIN) |
| Frequency Rresponse on axis | ±2 dB from 58 Hz - 22 kHz |
| Frequency Rresponse 30 off axis | ±2 dB from 58 Hz - 20 kHz |
| Sensitivity-Room/Anechoic | 92 dB / 88 dB |
| Suitable Amplifier Power Range | 160 - 15 watts |
| Maximum Input Power | 110 watts |
| Impedance | Compatible with 8 ohms |
| Height,Width or Diameter | 28.2 cm x19.4 cm / 11-1/8 in x7-5/8 in (Height x Width) |
| Minimum Mounting Depth | 7.4 cm /2-15/16 in |
| Cutout Dimensions | |
| Height x Width | 10-1/4 in x 6-3/4 in (Height x Width) |
| Minimum Internal Volume Required | 12 L / 0.4 cu ft |
| Pre-Installation Brackets | PB-7x10 |

| | |
|----------|------------------|
| Weight | 15.7lb / 7.10kg |
| Finishes | White, paintable |