

twenty[®].23



Your first impression of the **twenty.23** is of an open and engaging loudspeaker, its size defying both the depth of bass it can offer and the scale of its presentation — it takes any music or film material in its stride. The sound is vivid and dynamic and delivered with authority — with your eyes closed, the location of the speakers can be hard to determine. Such is the realism of the **twenty.23**'s sound.

"Despite its modest size, it does a remarkable job of delivering an essentially full bandwidth sound, with fine neutrality and excellent stereo imaging"

HI-FI CHOICE Jan '12

"If you're looking for a top-class pair of compact floorstanders, look no further"

WHAT HI-FI? SOUND AND VISION ★★★★★ Aug '12

The plinth

Isolated stabilising plinths de-couple the cabinet allowing greater stereo focus and tighter defined bass.



January '12



Awards '12



January '13



Awards '13

SPECIFICATIONS

twenty®21

Freq response	50Hz – 25kHz		
Sensitivity	87dB 1W 1m		
Recommended amp power	30 - 150W		
Effective ATL™	1.72m	5.6ft	
Impedance	8 Ohm		
Drive units	LF PMC twenty® series, lightweight doped 5.5"/140mm cone with cast alloy chassis HF PMC/SEAS®, 27mm twenty® series, SONOLEX™ Soft dome, Ferrofluid cooled		
Crossover freq	1.8kHz		
Input connectors	2 pairs 4mm sockets (Bi-amp or Bi-wire)		
Dimensions	H 325mm	12.8"	
	W 152mm	6.0"	
	D 277mm	11.0"	(+6mm grille)
Weight	5kg	11 lbs ea.	

twenty®22

Freq response	40Hz – 25kHz		
Sensitivity	90dB 1W 1m		
Recommended amp power	30 - 200W		
Effective ATL™	2.0m	6.5ft	
Impedance	8 Ohm		
Drive units	LF PMC twenty® series, lightweight doped 6.5"/170mm one with cast alloy chassis HF PMC/SEAS®, 27mm twenty® series, SONOLEX™ Soft dome, Ferrofluid cooled		
Crossover freq	1.8kHz		
Input connectors	2 pairs 4mm sockets (Bi-amp or Bi-wire)		
Dimensions	H 410mm	16.14"	
	W 184mm	7.25"	
	D 367mm	14.45"	(+6mm grille)
Weight	8kg	17.6 lbs ea.	

twenty®23

Freq response	29Hz – 25kHz		
Sensitivity	87dB 1W 1m		
Recommended amp power	30 - 150W		
Effective ATL™	2.4m	7.8ft	
Impedance	8 Ohm		
Drive units	LF PMC twenty® series, lightweight doped 5.5"/140mm cone with cast alloy chassis HF PMC/SEAS®, 27mm twenty® series, SONOLEX™ Soft dome, Ferrofluid cooled		
Crossover freq	1.8kHz		
Input connectors	2 pairs 4mm sockets (Bi-amp or Bi-wire)		
Dimensions	H 918mm	36.14"	(+25mm spikes)
	W 152mm	6.0"	
	D 330mm	13.0"	(+6mm grille)
Weight	13.2kg	29 lbs ea.	

twenty®24

Freq response	28Hz – 25kHz		
Sensitivity	90dB 1W 1m		
Recommended amp power	30 - 200W		
Effective ATL™	3.0m	9.8ft	
Impedance	8 Ohm		
Drive units	LF PMC twenty® series, lightweight doped 6.5"/170mm cone with cast alloy chassis HF PMC/SEAS®, 27mm twenty® series, SONOLEX™ Soft dome, Ferrofluid cooled		
Crossover freq	1.8kHz		
Input connectors	2 pairs 4mm sockets (Bi-amp or Bi-wire)		
Dimensions	H 1028mm	40.47"	(+25mm spikes)
	W 184mm	7.25"	
	D 419mm	16.5"	(+6mm grille)
Weight	21kg	46.2 lbs ea.	

THE STAND

The **twenty®** stand shares its design with PMC's advanced twenty5 range, and has been engineered to optimise the imaging, dynamics and overall tonal balance by using a blend of an ultra-rigid structure and resonance absorbing materials. The front tube can be filled to 'tune' the stand providing not only greater stability and mass but better bass definition. The rear tube is internally damped and allows cables to be passed through, maintaining a clean, elegant line.

H 599mm 23.5" (+25mm spikes) **W** 229mm 9.0" **D** 364mm 14.3"

